

MATERIAL STANDARD**TAPE, MASKING
PRESSURE SENSITIVE**

Scope: This specification covers high performance pressure-sensitive masking tape consisting of a pressure-sensitive adhesive on crepe paper backing.

Applicable Specification: Except as modified by this specification, the tape shall meet the requirements of Federal Specification UU-T-106, Type I, latest revision.

Clean Stripping: When applied to a properly painted surface, this tape shall strip clean, leaving no film or residue and shall not strip off or remove any of the underlying paint coating.

Physical Properties:

Thickness, maximum 7.5 mils
Tensile strength, longitudinal pounds per inch of width, minimum 19 lbs.
Ultimate elongation, minimum 10 per cent
Adhesion to steel, min. ounces per inch width 30 ounces

Packaging: The tape shall be uniformly and smoothly wound in 60-yard rolls on a suitable core having an inside diameter of $3 \pm 1/32$ inches. The tape shall be packaged with wax paper separators (or equivalent) between rolls.

Reference Specification: Fed. Spec. UU-T-106, Type I, latest revision

Stock Unit: RL

			Approved Manufacturer	
			3M	
			Product No.	Part No. (UPC)
Stock Number	Width, Inches	Packaging Rolls/Case		
736702	3/4 (18 mm)	48	233+	26334
736704	1 (24 mm)	24	233+	26336
736710	2 (48 mm)	12	233+	26340

ORIGINATOR	STANDARDS COORDINATOR	STANDARDS SUPERVISOR	UNIT DIRECTOR
<i>Jim S. Horn</i>	<i>Charles L. Shaffer</i>	<i>John C. Himmer</i>	<i>Harold J. Jy</i>